Karakteristike



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Önálló ház horganyzott acéllemezb?l, szerkezeti epoxi-poliészter festéssel, alapkivitelben RAL9016 fehér színben.Megrendelésre kérhet? egyéb színekben vagy rozsdamentes acélból.
- Széles bemeneti rács csiszolt élekkel, mely nem igényel komoly karbantartást.
- Eloxált alumínium kimeneti lapátok szárnykialakítással, mindkét oldalon 0 és 15º között állítható.
- Kett?s bemeneti centrifugális ventilátorok, küls? rotor motorral és alacsony zajszinttel. 5 sebességfokozat.Az EC modellek rendkívül alacsony fogyasztású hatékony ventilátorokkal szerelve.
- „A” típus f?tés nélkül, kizárólag leveg?vel.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  • Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  • Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Specifikacije

50Hz

Model	Neogrevano	
	(m³/h)	(m)
TWIN KECG 3000 A	9,8-13,8	
TWIN KM 1500 A	9,8-13,1	
TWIN KM 2000 A	9,8-13,1	
TWIN KM 2500 A	9,8-13,1	
TWIN KM 3000 A	9,8-13,1	
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	
TWIN KG 1500 A	9,8-13,1	
TWIN KG 2000 A	9,8-13,1	
TWIN KG 2500 A	9,8-13,1	
TWIN KG 3000 A	9,8-13,1	
TWIN KECG 1500 A	9,8-13,8	
TWIN KECG 2000 A	9,8-13,8	
TWIN KECG 2500 A	9,8-13,8	

60Hz

Neogrevano

Model	(m³/h)	(m)
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	

Dimenzije

